

## Model 1000NC Builder Series Heat / Cool

Non-Programmable



- Bright Blue Display Backlight
- Easy Access Front Battery Door
- Battery Powered with Latching Relay Output
- Compressor Short Cycle Protection
- Adjustable Temperature Differential
- ESD Guard™ Electronic Circuitry

The  
brighter  
choice®

**2** YEAR  
LIMITED  
WARRANTY

### Specifications

<b>Product Dimensions:</b>	3.67" x 4.72" x 1.17"
<b>Electric Rating:</b>	24 Volt AC (18-30 Volts AC) 1 amp maximum load per terminal 2 amp total maximum load (all terminals)
<b>Control Range:</b>	45° to 90° F (7° to 32° C)
<b>Accuracy:</b>	+/- 1° F (+/- .5° C)
<b>DC Power:</b>	3.0 Volts DC (2 "AA" Alkaline batteries included)
<b>Compatibility:</b>	Single stage gas, oil or electric systems (including single stage heat pumps and millivolt heat only systems)
<b>Terminations:</b>	Rh, Rc, O/B, Y, W, G

### Shipping Information

<b>INDIVIDUAL CARTON</b>	<b>MASTER CARTON</b>
<b>Dimensions:</b> 3.75" x 5.50" x 1.44"	<b>Quantity:</b> 12
<b>Weight:</b> .45 lbs.	<b>Dimensions:</b> 6.00" x 4.50" x 17.00"
	<b>Cubic Feet:</b> 0.27
	<b>Weight:</b> 5.8 lbs.

### Accessories

2950 Universal Wall Plate (6.5" x 6.5" x .125")  
5970 Universal Thermostat Guard

### Braeburn 1000NC Replaces

<b>Honeywell®</b>	T8400, T8401*, T8034*, T834*, T87F*
<b>White-Rodgers®</b>	1F78-144, 1F56*, 1D56*, 1E56*, 1F51*
<b>Robertshaw®</b>	8400-1, 8401-1*, 9400, 9401*, 9405*, 9500*, 9505*, 9200*
<b>ICM®</b>	SC1600*, SC1601*, SC1800*, SC1801*, SC1900*, SC1901*, SC2000, SC2001*
<b>LuxPro®</b>	PSD100, PSD111, PSD150, PSD152*, PSD158*

\*Verify specific single stage application requirements.  
All trademarks are the property of their respective owners.