

Braeburn®

Model 1005NC Builder Series Universal Heat Only or Cool Only

Non-Programmable

- Bright Display Backlight
- Easy Access Front Battery Door
- Battery Powered with Latching Relay Output
- Compressor Short Cycle Protection
- Adjustable Temperature Differential
- ESD Guard™ Electronic Circuitry



The
brighter
choice®

2 YEAR
LIMITED
WARRANTY

Specifications

Product Dimensions:	3.67" x 4.72" x 1.17"
Electric Rating:	24 Volt AC (18-30 Volts AC) 1 amp maximum load per terminal 2 amp total maximum load (all terminals)
Control Range:	45° - 90° F (7° - 32° C)
Accuracy:	+/- 1° F (+/- .5° C)
DC Power:	3.0 Volts DC (2 "AA" Alkaline batteries included)
Compatibility:	Single stage gas, oil or electric systems (including millivolt heat only systems)
Terminations:	R, W/Y, G

Shipping Information

INDIVIDUAL CARTON	MASTER CARTON
Dimensions: 3.75" x 5.50" x 1.44"	Quantity: 12
Weight: .45 lbs.	Dimensions: 6.00" x 4.50" x 17.00"
	Cubic Feet: 0.27
	Weight: 5.8 lbs.

Accessories

2950 Universal Wall Plate (6.5" x 6.5" x .125")
5970 Universal Thermostat Guard

Braeburn 1005NC Replaces

Honeywell®	T8400*, T87F*, T810C, T810D, T812A, T812B, T822*
White-Rodgers®	1F51, 1E30, 1E31, 1F30, 1F36, 1C30, 1D30, 1C20, 1C21
Robertshaw®	9405, 9505, 9204, 9206, 986-1, 984-1
ICM®	SC1600, SC1601, SC1800, SC1801, SC1900, SC1901
LuxPro®	PSD158, PSM30S, PSM50, PSM200SA

*Verify specific single stage application requirements.
All trademarks are the property of their respective owners.