

Braeburn®

Model 2000NC Builder Series Heat / Cool

Programmable



- 5-2 Day Separate Weekday / Weekend Programming
- Large Display with Bright Blue Backlight
- Battery Powered with Latching Relay Output
- Non-Volatile Memory to Maintain User Settings
- Filter Check Monitor
- Adaptive Recovery Mode (ARM™)
- Adjustable Temperature Differential
- ESD Guard™ Electronic Circuitry
- Separate Heating and Cooling Set Point Program Times and Temperatures
- Temporary Program Override for 4 Hours or Until Next Set Point
- Programmable Extended Hold Mode
- Compressor Short Cycle Protection
- Easy Access Front Battery Door

The
brighter
choice®



2 YEAR
LIMITED
WARRANTY

Specifications

Product Dimensions:	3.67" x 4.72" x 1.17"
Electric Rating:	24 Volt AC (18-30 Volts AC) 1 amp maximum load per terminal 2 amp total maximum load (all terminals)
Control Range:	45° to 90° F (7° to 32° C)
Accuracy:	+/- 1° F (+/- .5° C)
DC Power:	3.0 Volts DC (2 "AA" Alkaline batteries included)
Compatibility:	Single stage gas, oil or electric systems (including single stage heat pumps and millivolt heat only systems)
Terminations:	Rh, Rc, O/B, Y, W, G

Shipping Information

INDIVIDUAL CARTON	MASTER CARTON
Dimensions: 3.75" x 5.50" x 1.44"	Quantity: 12
Weight: .45 lbs.	Dimensions: 6.00" x 4.50" x 17.00"
	Cubic Feet: 0.27
	Weight: 5.8 lbs.

Accessories

2950 Universal Wall Plate (6.5" x 6.5" x .125")
5970 Universal Thermostat Guard

Braeburn 2000NC Replaces

Honeywell®	TH6100*, TH6110*, T8000*, T8112*, T8131, T8132
White-Rodgers®	1F78-151*
Robertshaw®	8600-1*, 8601-1, 9600*
ICM®	SC3000*, SC3001*, SC3006*
LuxPro®	PSP211*, PSP511*, PSP511L*, PSP600*, PSP700*

*Verify specific single stage application requirements.
All trademarks are the property of their respective owners.