Braeburn.

7320

Up to 3 Heat / 2 Cool Heat Pump Up to 2 Heat / 2 Cool Conventional

Smart Wi-Fi Universal Thermostat



Phone not included.

Thermostat Features

- 7 Day, 5-2 Day or Non-Programmable
- Large 6.5 sq. in. Easy-Read Touchscreen
- Bright Blue Backlight Display
- Auto or Manual Changeover
- Residential or Commercial Modes
- Adjustable Temperature Limits
- Wireless or Wired Remote Sensing
- · Auxiliary Heat Fossil Fuel Option
- Hardwire or Battery Powered
- Humidification and Dehumidification Control with 7330 Wireless Sensor
- Auxiliary "A" Terminal for Economizer, Fresh Air or Output Control
- Common "C" wire required to use Wi-Fi

FREE Color Contractor Branding! Visit braeburnonline.com

Application Features

- · Compatible with Virtually All Smartphones, Tablets or PC's
- Multi-Color Program Groups Simplify Scheduling
- Flexible Vacation and Holiday Scheduling
- Text and E-Mail Service and Temperature Alerts
- BlueLink QuickCopy® Allows User to Duplicate Program Program and Configuration to Other Thermostats
- QuickEdit® Makes Schedule Changes Easy
- BlueLink SmartData® Energy Report Capability
- Monitor and Control Multiple Thermostats
- View Outdoor Temperature*
- Adjust and View Indoor Humidity*
- Easy Access Dealer Information
- Optional Geofencing for Increased Energy Savings





Compatible with Amazon Alexa

Amazon Alexa is a trademark of Amazon.com, Inc.



www.braeburnonline.com

*Optional sensor required.

Braeburn.



BlueLink Smart Connect Application Screens

FREE app to monitor and control multiple thermostats from virtually any Smartphone, Tablet or PC

Multi-Color Program Groups



Vacation and Holiday Scheduling



Geofencing



BlueLink QuickCopy® Feature



BlueLink SmartData® Reports



Service and Temperature Alerts





BlueLink Service Connect Application Screens

FREE app for contractors, allowing them the ability to monitor and manage multiple customer thermostats







Product Specifications

Dimensions: 3.8" x 5.56" x 1.19" **Electric Rating:** 24 Volt AC (18-30 Volt AC)

> 1 amp maximum load per terminal 6 amp total maximum load (all terminals)

AC Power: 18-30 Volt AC (required for Wi-Fi)

DC Power: 3.0 Volts DC

(2 "AA" Alkaline batteries included)

Compatibility: Heat pump systems up to 3 heat/2 cool,

Conventional systems up to 2 heat/2 cool

Wi-Fi Communication: 802.11 (requires 24 VAC with C wire)

Control Range: 45° to 90° F (7° to 32° C) **Display Range:** 40° to 99° F (5° to 37° C)

Accuracy: +/- 1° F (+/- .5° C)

Terminations: Rh, Rc, C, W2/AUX, W1/E, L, A, O/B, G, Y2, Y1, K, S2, S1

Shipping Information

INDIVIDUAL CARTON

Dimensions: 5.0" x 6.0" x 2.5"

Weight: 1.2 lbs **MASTER CARTON** Quantity:

Dimensions: 7.25" x 6.25" x 5.4"

Cubic Feet: .14 Weight: 3.85 lbs.

Braeburn 7320 Replaces*

Honeywell® TH8320WF, TH6320WF. Pro1® T855i, T701i

TH9320WF, TH8732WF **Nest®** T100577, T200577, T3007ES

1F86U-42WF Venstar® T7850, T7900

*Verify specific application requirements. All trademarks are the property of their respective owners.

Accessories

7330 Wireless Remote Humidity Sensor

7340 Share-a-Wire® Module

7390 Wireless Remote Indoor Sensor 7490 Wireless Remote Outdoor Sensor

2920 Vertical J-Box Adapter Wall Plate

2950 Universal Wall Plate (6.5" x 6.5") 5390 Wired Remote Indoor Sensor 5490 Wired Remote Outdoor Sensor

5970 Universal Thermostat Guard

(6.5" x 5.1")



Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Google and Google Play are trademarks of Google LLC. Amazon, Alexa and all related logos are trademarks of Amazon.com. Inc. or its affiliates

FREE Contractor

Visit our website (www.braeburnonline.com) for more information, contact your local distributor Branding Available! or call our sales department toll-free at 866.268.5599 (U.S.), +1.630.844.1968 (Outside the U.S.)