

Braeburn®

7320

Up to 3 Heat / 2 Cool Heat Pump
Up to 2 Heat / 2 Cool Conventional
Smart Wi-Fi Universal Thermostat



BlueLink
smart connect



5 YEAR
LIMITED
WARRANTY



Phone not included.

Thermostat Features

- 7 Day, 5-2 Day or Non-Programmable
- Large 6.5 sq. in. Easy-Read Touchscreen
- Bright Blue Backlight Display
- Auto or Manual Changeover
- Residential or Commercial Modes
- Adjustable Temperature Limits
- Wireless or Wired Remote Sensing
- Auxiliary Heat Fossil Fuel Option
- Hardwire or Battery Powered
- Humidification and Dehumidification Control with 7330 Wireless Sensor
- Auxiliary "A" Terminal for Economizer, Fresh Air or Output Control
- Common "C" wire required to use Wi-Fi

Application Features

- Compatible with Virtually All Smartphones, Tablets or PC's
- Multi-Color Program Groups Simplify Scheduling
- Flexible Vacation and Holiday Scheduling
- Text and E-Mail Service and Temperature Alerts
- BlueLink QuickCopy® Allows User to Duplicate Program Program and Configuration to Other Thermostats
- QuickEdit® Makes Schedule Changes Easy
- BlueLink SmartData® Energy Report Capability
- Monitor and Control Multiple Thermostats
- View Outdoor Temperature*
- Adjust and View Indoor Humidity*
- Easy Access Dealer Information
- Optional Geofencing for Increased Energy Savings



Compatible with Amazon Alexa
Amazon Alexa is a trademark of Amazon.com, Inc.

works with the
Google Assistant

www.braeburnonline.com

*Optional sensor required.

FREE Color Contractor Branding!
Visit braeburnonline.com

Toll-Free 866.268.5599 (U.S.) +1.630.844.1968 (Outside the U.S.)

Braeburn®



BlueLink Smart Connect® Application Screens

FREE app to monitor and control multiple thermostats from virtually any Smartphone, Tablet or PC


Multi-Color Program Groups



Vacation and Holiday Scheduling



Geofencing



BlueLink QuickCopy® Feature



BlueLink SmartData® Reports




Service and Temperature Alerts



BlueLink Service Connect® Application Screens

FREE app for contractors, allowing them the ability to monitor and manage multiple customer thermostats



Product Specifications

Dimensions:	3.8" x 5.5" x 1.19"
Electric Rating:	24 Volt AC (18-30 Volt AC) 1 amp maximum load per terminal 6 amp total maximum load (all terminals)
AC Power:	18-30 Volt AC (required for Wi-Fi)
DC Power:	3.0 Volts DC (2 "AA" Alkaline batteries included)
Compatibility:	Heat pump systems up to 3 heat/2 cool, Conventional systems up to 2 heat/2 cool
Wi-Fi Communication:	802.11 (requires 24 VAC with C wire)
Control Range:	45° to 90° F (7° to 32° C)
Display Range:	40° to 99° F (5° to 37° C)
Accuracy:	+/- 1° F (+/- .5° C)
Terminations:	Rh, Rc, C, W2/AUX, W1/E, L, A, O/B, G, Y2, Y1, K, S2, S1

Shipping Information

INDIVIDUAL CARTON		MASTER CARTON
Dimensions:	5.0" x 6.0" x 2.5"	Quantity: 3
Weight:	1.2 lbs.	Dimensions: 7.25" x 6.25" x 5.4"
		Cubic Feet: .14
		Weight: 3.85 lbs.

Braeburn 7320 Replaces*

Honeywell®	TH8320WF, TH6320WF, TH9320WF, TH8732WF	Pro1®	T855i, T701i
Emerson®	1F86U-42WF	Nest®	T100577, T200577, T3007ES
		Venstar®	T7850, T7900

*Verify specific application requirements. All trademarks are the property of their respective owners.

Accessories

7330	Wireless Remote Humidity Sensor	2950	Universal Wall Plate (6.5" x 6.5")
7340	Share-a-Wire™ Module	5390	Wired Remote Indoor Sensor
7390	Wireless Remote Indoor Sensor	5490	Wired Remote Outdoor Sensor
7490	Wireless Remote Outdoor Sensor	5970	Universal Thermostat Guard
2920	Vertical J-Box Adapter Wall Plate (6.5" x 5.1")		

FREE Contractor Branding Available!

Visit our website (www.braeburnonline.com) for more information, contact your local distributor or call our sales department toll-free at 866.268.5599 (U.S.), +1.630.844.1968 (Outside the U.S.).



Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Google and Google Play are trademarks of Google LLC. Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates.